


STRAIGHT


millimetres
inches



Thread A	Dim. B		Dim. C		Dim. D		Part No.
2 BA	3.7	.15	8.8	.35	6.7	.265	NA 5714 *
1/4" B.S.F.	5.6	.22	8.3	.33	7.9	.312	NA 5725†
1/4" B.S.F.	5.6	.22	8.3	.33	7.9	.312	NA 5700/1
5/16" B.S.F.	6.4	.25	10.5	.42	9.5	.375	NA 5702/1
3/8" B.S.F.	6.4	.25	10.5	.42	11.1	.437	NA 5706/1
1/8" B.S.P.F.	6.4	.25	10.5	.42	11.1	.437	NA 5704
1/8" B.S.P.F.	6.4	.25	10.5	.42	11.1	.437	NA 5723*
1/4" B.S.P.F.	10.4	.41	12.2	.48	13.3	.525	NA 5707/1
1/4" B.S.W.	5.6	.22	8.3	.33	7.9	.312	NA 5700/2
5/16" B.S.W.	6.4	.25	10.5	.42	9.5	.375	NA 5702/2
1/8" - 27 N.P.T.	6.0	.24	13.2	.52	11.1	.437	NA 5729
1/8" - 27 N.P.T.	8.6	.34	10.5	.42	11.1	.437	NA 5703
1/4" - 18 N.P.T.	10.4	.41	12.2	.48	14.3	.562	NA 5721
1/4" - 28 U.N.F.	5.6	.22	8.3	.33	7.9	.312	NA 6625
1/4" - 28 U.N.F.	5.6	.22	9.8	.39	7.9	.312	NA 6688
5/16" - 24 U.N.F.	6.4	.25	10.5	.42	9.5	.375	NA 6627
3/8" - 24 U.N.F.	6.4	.25	10.5	.42	11.1	.437	NA 6629
1/4" Self tapping	5.3	.21	8.5	.34	7.9	.312	NA 6697
3/16" nom Drive fit	5.6	.22	8.3	.33	9.5	.375	NA 6607
1/4" nom Drive fit	5.6	.22	8.3	.33	9.5	.375	NA 5766
5/16" nom Drive fit	5.6	.22	11.3	.45	9.5	.375	NA 5767
5/16" nom Drive fit	4.9	.19	11.0	.43	9.5	.375	NA 5769 *
5/16" nom serrated Drive fit	6.5	.26	7.4	.29	9.5	.375	NA 5777
5 mm nom serrated Drive fit	5.2	.21	7.1	.28	7.9	.312	NA 5779 *
7/32" nom serrated Drive Fit	5.7	.23	8.1	.32	8.0	.31	NA 5778
M6 x 1.00 Taper	6.1	.24	9.3	.37	7.0	.28	NA 7006
M8 x 1.00 Taper	6.1	.24	9.3	.37	9.0	.35	NA 7007
M8 x 1.25 Taper	6.1	.24	9.3	.37	9.0	.35	NA 7008
M10 x 1.00 Taper	6.1	.24	9.3	.37	11.0	.43	NA 7009
M10 x 1.50 Taper	6.1	.24	9.3	.37	11.0	.43	NA 7010

Not illustrated 1/8" B.S.P.F. Water Pump Plug 7.3 .29 19.7 .78 11.1 .437 NA 5709/2

All drive fit nipples are manufactured from round bar, and dimension D equals bar diameter.



1/4" B.S.F.	7.4	.29	21.8	.86	6.7	.265	NA 5717
1/4" - 28 U.N.F.	9.4	.37	46.9	1.85	7.9	.312	NA 6630
1/4" - 28 U.N.F.	7.4	.29	21.8	.86	6.7	.265	NA 6639